

CLAIMS

This claim list will replace all prior versions and lists of claims in the application.

1. (Previously Presented) A method for automatically entering into a secure communication mode in a wireless communication terminal, comprising the steps of:
 - a) storing a voice signal outputted from a vocoder of the wireless communication signal for a predetermined time;
 - b) selecting at least one of the signal values among which the occurrence of generation is lower than a threshold value, to generate a token header data;
 - c) combining token header data of variable lengths to form a token header and generating a token including the token header, the token header data having the lowest occurrence of generation among voice data outputted from a vocoder of the wireless communication terminal;
 - d) at a transmission terminal, receiving a request for a secure communication from a user and transmitting the token to a reception terminal; and
 - e) at the transmission terminal, entering into a secure communication mode based on an acknowledge token transmitted from the reception terminal, and performing secure communication with the reception terminal.
2. (Previously Presented) The method as recited in claim 1, wherein the token includes a data having the lowest generation occurrence among the data of voice packet data outputted from the vocoder as a token header.
3. (Original) The method as recited in claim 1, wherein the token is shorter than the maximum length of the data outputted from the vocoder.

4. (Original) The method as recited in claim 3, wherein the token includes a key used in an encryption algorithm for the secure communication.

5. (Previously Presented) The method as recited in claim 1, wherein in the step d), the token is transmitted repeatedly a predetermined number of times.

6. (Previously Presented) The method as recited in claim 5, wherein in the step d), the repeated transmission of the token stops when the acknowledge token transmitted from the reception terminal is received.

7. (Previously Presented) The method as recited in claim 1, further comprising the steps of:

f) at the reception terminal, checking out if the token transmitted from the transmission terminal is received, and transmitting the token formed in the step a) as an acknowledge token to the transmission terminal; and

g) at the reception terminal, entering into a secure communication mode and performing secure communication with the transmission terminal.

8. (Original) The method as recited in claim 7, wherein the step f) includes the step of:

h) checking out if a session key generated in the transmission terminal and included in the token is matched with a session key generated in the reception terminal using a master key.

9. (Previously Presented) A computer-readable recording medium for recording a program that implements a method for automatically entering into a secure communication

mode in a wireless communication terminal provided with a processor, comprising the steps of:

- a) combining token header data of variable lengths to form a token header and generating a token including the token header, the token header data having the lowest occurrence of generation among voice data outputted from a vocoder of the wireless communication terminal;
- b) at a transmission terminal, receiving a request for a secure communication from a user and transmitting the token to a reception terminal; and
- c) at the transmission terminal, entering into a secure communication mode based on an acknowledge token transmitted from the reception terminal, and performing secure communication with the reception terminal.

10. (Previously Presented) The method of claim 1, further comprising:
combining the token header data to form the token header of a predetermined length.